

9/19/7

DIALOG(R)File 347:JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

05720112 **Image available**

TONER SEALING MECHANISM FOR BEARING

PUB. NO.: 10-003212 [JP 10003212 A]

PUBLISHED: January 06, 1998 (19980106)

INVENTOR(s): MIHASHI HIROSHI

 MATSUI YOSUKE

 IKUMA KENJI

APPLICANT(s): BANDO CHEM IND LTD [000506] (A Japanese Company or Corporation), JP (Japan)

APPL. NO.: 08-156768 [JP 96156768]

FILED: June 18, 1996 (19960618)

INTL CLASS: [6] G03G-015/08; G03G-015/08; F16J-015/32

JAPIO CLASS: 29.4 (PRECISION INSTRUMENTS -- Business Machines); 14.2
 (ORGANIC CHEMISTRY -- High Polymer Molecular Compounds); 22.1
 (MACHINERY -- Machine Elements)

ABSTRACT

PROBLEM TO BE SOLVED: To maintain excellent sealing performance for a long time and to make structure inexpensive and compact by disposing a toner sealing member consisting of a shaft sealing part, a housing sealing part, and a side surface coating part making a bearing get out of contact with toner and connecting and integrating both sealing parts on the bearing.

SOLUTION: A contact side on the inner surface of the bearing 1 with the toner is cylindrically hollowed out so as to form a space. In the space, the shaft sealing part 7 having an elastic lip 6 is arranged in an abutting state on a rotary shaft so that the edge of the lip 6 is faced to a toner housing side. The toner sealing member 2 is composed of the shaft sealing part 7, the side surface coating part 8 and the housing sealing part 9, attached so that the contact side surface of the bearing 1 with the toner may be coated, and a projected part 9a is formed on the housing sealing part 9. The housing part 9 is allowed to lie in a gap between the housing side plate and the outer periphery of the bearing 1 and the projected part 9a is fit in the recessed part of the housing side plate, so that airtightness is secured.

C:\Program Files\Dialog\DialogLink\Graphics\44.bmp

